


SOT-23-6L Plastic-Encapsulate MOSFETS

CJL8205 Dual N-Channel MOSFET

$V_{BR,DSSS}$	$R_{DS(on)}\text{MAX}$	I_D
19V	25mΩ@4.5V	6A
	32mΩ@2.5V	




FEATURE

- TrenchFET Power MOSFET
- Excellent $R_{DS(on)}$
- Low Gate Charge
- High Power and Current Handling Capability
- Surface Mount Package


APPLICATION

- Battery Protection
- Load Switch
- Power Management

MARKING



Equivalent Circuit



ABSOLUTE MAXIMUM RATINGS ($T_s=25^\circ\text{C}$ unless otherwise noted)

Parameter	Symbol	Value	Unit
Drain-Source Voltage	V_{DS}	19	V
Gate-Source Voltage	V_{GS}	± 10	V
Continuous Drain Current	I_D	6	A
Pulsed Drain Current (note 1)	$I_{D(\text{p})}$	25	A
Thermal Resistance from Junction to Ambient (note 2)	R_{JA}	357	°C/W
Junction Temperature	T_J	150	°C
Storage Temperature	T_{STO}	-55~150	°C
Lead Temperature for Soldering Purposes(1/8" from case for 10 s)	T_L	260	°C

MOSFET ELECTRICAL CHARACTERISTICS

T_a=25 °C unless otherwise specified


Parameter	Symbol	Test Condition	Min	Typ	Max	Unit
STATIC CHARACTERISTICS						
Drain-source breakdown voltage	V _{(DSS)BD}	V _{DS} = 0V, I _D = 250µA	19			V
Zero gate voltage drain current	I _{DS}	V _{DS} = 18V, V _G = 0V			1	µA
Gate-body leakage current	I _{GS}	V _G = ±10V, V _{DS} = 0V			±100	nA
Gate threshold voltage (note 3)	V _{GS(th)}	V _{DS} = V _{GS} , I _D = 250µA	0.5		0.9	V
Drain-source on-resistance (note 3)	R _{DS(on)}	V _{DS} = 4.5V, I _D = 6A			25	mΩ
		V _{DS} = 2.5V, I _D = 5A			32	mΩ
Forward transconductance (note 3)	g _{FS}	V _{DS} = 5V, I _D = 4.5A		10		S
Diode forward voltage (note 3)	V _{SD}	I _D = 1.25A, V _{DS} = 0V			1.2	V
DYNAMIC CHARACTERISTICS (note4)						
Input Capacitance	C _{iss}	V _{DS} = 8V, V _G = 0V, f = 1MHz		800		pF
Output Capacitance	C _{oss}			155		pF
Reverse Transfer Capacitance	C _{rss}			125		pF
SWITCHING CHARACTERISTICS (note 4)						
Turn-on delay time	t _{on}	V _{DD} = 10V, V _{GS} = 4V, I _D = 1A, R _{LOAD} = 1Ω		18		ns
Turn-on rise time	t _r			5		ns
Turn-off delay time	t _{off}			43		ns
Turn-off fall time	t _f			20		ns
Total Gate Charge	Q _g	V _{DS} = 10V, V _G = 4.5V, I _D = 4A		11		nC
Gate-Source Charge	Q _{gs}			2.3		nC
Gate-Drain Charge	Q _{gd}			2.5		nC

Notes :


- 1.Repetitive rating: Pulse width limited by maximum junction temperature
- 2.Surface Mounted on FR4 board, t ≤ 10 sec.
3. Pulse test : Pulse widths 300µs, duty cycle≤2%.
4. Guaranteed by design, not subject to production.

Typical Characteristics


Output Characteristics




Transfer Characteristics




$R_{DS(on)}$ — I_D




$R_{DS(on)}$ — V_{GS}




I_S — V_{SD}



Threshold Voltage




SOT-23-6L Package Outline Dimensions



Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min.	Max.	Min.	Max.
A	1.050	1.250	0.041	0.049
A1	0.000	0.100	0.000	0.004
A2	1.050	1.150	0.041	0.045
b	0.300	0.500	0.012	0.020
c	0.100	0.200	0.004	0.008
D	2.820	3.020	0.111	0.119
E1	1.500	1.700	0.059	0.067
E	2.650	2.950	0.104	0.116
e	0.950(BSC)		0.037(BSC)	
e1	1.800	2.000	0.071	0.079
L	0.300	0.600	0.012	0.024
θ	0°	8°	0°	8°

SOT-23-6L Suggested Pad Layout



Note:


1. Controlling dimension: in millimeters.
2. General tolerance: $\pm 0.05\text{mm}$.
3. The pad layout is for reference purposes only.

NOTICE

JCET reserve the right to make modifications,enhancements, improvements, corrections or other changes without further notice to any product herein.JCET does not assume any liability arising out of the application or use of any product described herein.

SOT-23-6L Tape and Reel

SOT-23-6L Embossed Carrier Tape




Packaging Description:


SOT-23-6L parts are shipped in tape. The carrier tape is made from a dissipative (carbon filled) polycarbonate resin. The cover tape is a multilayer film (Heat Activated Adhesive in nature) primarily composed of polyester film, adhesive layer, sealant, and anti-static sprayed agent. These reeled parts in standard option are shipped with 3,000 units per 7" or 18.0cm diameter reel. The reels are clear in color and is made of polystyrene plastic (anti-static coated).

Pkg type	Dimensions are in millimeter									
	a	B	C	d	E	F	P0	P	P1	W
SOT-23-6L	3.17	3.23	1.37	Ø1.55	1.75	3.50	4.00	4.00	2.00	8.00

SOT-23-6L Tape Leader and Trailer



SOT-23-6L Reel



Dimensions are in millimeter								
Reel Option	D	D1	D2	G	H	I	W1	W2
7" Dia	Ø180.00	60.00	13.00	R78.00	R25.60	R6.50	9.50	13.10

REEL	Reel Size	Box	Box Size(mm)	Carton	Carton Size(mm)	G.W.(kg)
3000 pcs	7 inch	30,000 pcs	203×203×195	120,000 pcs	436×436×220	