

MB1FAT THRU MB10FAT

SURFACE MOUNT BRIDGE RECTIFIERS

Forward Current-0.8A Reverse Voltage-100V to 1000V

FEATURES


- ◆ For surface mount applications
- ◆ Glass passivated chip junction
- ◆ Reverse voltage: 100V to 1000V
- ◆ Forward current: 0.8A
- ◆ High surge current capability

MECHANICAL DATA

- ◆ Case: MBF molded plastic body
- ◆ Terminals:Solderable per MIL-STD-750,Method 2026
- ◆ Weight: Approximated 0.075grams

PINNING

PIN	DESCRIPTION
1	Input Pin (~)
2	Input Pin (~)
3	Output Anode (+)
4	Output Cathode (-)



MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Ratings at 25°C ambient temperature unless otherwise specified.

Single phase half-wave 60 Hz, resistive or inductive load, for capacitive load current derating by 20 %.

PARAMETER	SYMBOL	MB1FAT	MB2FAT	MB4FAT	MB6FAT	MB8FAT	MB10FAT	UNIT
Maximum Repetitive Peak Reverse Voltage	V_{RRM}	100	200	400	600	800	1000	V
Maximum RMS Voltage	V_{RMS}	70	140	280	420	560	700	V
Maximum DC Blocking Voltage	V_{DC}	100	200	400	600	800	1000	V
Maximum Average Forward Rectified Current at $T_c = 125^\circ\text{C}$	$I_{F(AV)}$	0.8						A
Peak Forward Surge Current(Note1)	I_{FSM}	30						A
Maximum Forward Voltage at 0.8 A	V_F	1.1						V
Maximum DC Reverse Current at Rated DC Blocking Voltage $T_A=25^\circ\text{C}$ $T_A=150^\circ\text{C}$	I_R	5 40						μA
Typical Junction Capacitance(Note2)	C_J	13						pF
Typical Thermal Resistance(Note3)	$R_{\theta JA}$ $R_{\theta JC}$	90 30						$^\circ\text{C/W}$
Operating and Storage Temperature Range	T_J, T_{STG}	-55 to +150						$^\circ\text{C}$

Notes: 1. Measured at 8.3 ms single half sine wave superimposed on rated load (JEDEC Method).

2. Measured at 1MHz and applied reverse voltage of 4 V D.C.

3. Mounted on glass epoxy PC board with 1.5"×1.5" (3.81×3.81 cm) copper pad .

Dated: 03/2016

Rev:1.0

MB1FAT THRU MB10FAT

RATINGS AND CHARACTERISTIC CURVES

Fig.1 Average Rectified Output Current Derating Curve




Fig.2 Typical Reverse Characteristics




Fig.3 Typical Instantaneous Forward Characteristics




Fig.4 Typical Junction Capacitance






Fig.5 Maximum Non-Repetitive Peak Forward Surge Current



MB1FAT THRU MB10FAT

PACKAGE OUTLINE

MBF



MBF mechanical data

UNIT		A	C	D	E	H _E	d	e	L	L ₁	a	$\angle$
mm	max	1.6	0.22	5.0	4.1	7.0	2.7	0.8	1.7	1.1	0.2	7°
	min	1.2	0.15	4.5	3.6	6.4	2.3	0.5	1.3	0.5	—	
mil	max	63	8.7	197	161	276	106	31	67	43	8	
	min	47	5.9	177	142	252	91	20	51	20	—	

ORDERING INFORMATION

Device	Package	Shipping
MB1FAT thru MB10FAT	MBF	3,000/Tape & Reel (11 inches)
		5,000/Tape & Reel (13 inches)